

Data sheet

BenQ MX528

XGA Data-/ Video projector

- XGA 1024 x 768
- 3.300 ANSI-Lumens
- 3D via HDMI
- Smart Eco



Technology

Type : DLP™
Native Resolution: XGA 1024 x 768
Brightness: 3.300 ANSI-Lumens
max. Contrast : 13.000:1
Display Color: 1,07 Billion
Aspect Ratio: Physical 4:3 (5 aspect ratio selectable)
Cooling system : Front - ,Side ventilation, Quick cooling

Lamp

Type : 190 W
Lamp life : 4.500h Normal
10.000h Smart Eco Lamp Care Mode

Objective

Warranty : 12 Months or 2000h
Characteristics : Manual Zoom
Image Size (Diagonal): 1,52 m – 7,62 m
Lens : F=2.56-2.8, f=21-23.1 mm
Throw ratio: 1.96-2.15 (78°@3.1m)
Zoom : 1,1:1

Signal

Video Compatibility: NTSC/ PAL/SECAM
Video - Modi : 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
PC Resolution : VGA (640 x 480) bis UXGA (1600 x 1200)
Frequencies H/V : 31-102 kHz / 23-144 Hz
Input :
Composite Video 1 x RCA Cinch
S-Video 1 x Mini Din 4 pin
Component Video 2 x via D-Sub 15 pin
Audio 1 x Stereo Mini Jack
RGB VGA-Analog 2 x D-sub 15 pin
HDMI 1 x HDMI
USB 1x USB Type B (Page up/down)
Serial input : RS232 1 x D-Sub 9 pin
Output : RGB VGA-Analog 1 x D-sub 15 pin
Audio out 1 x Stereo Mini Jack

Control

Speaker : 1 x 2 Watt
Functions : 3D via HDMI , Brilliant Color™, 3-D-Colormangement, 2x digital Zoom, Wall color correction, Key log, Blank, Auto Off, Password security, OSD FAQ, 6-Segment-Color wheel (RYWCBG)

Security Energy

OSD: 28 Languages
Remote : IR-Remote Control
Certificates : CE, TÜV-GS
Power Supply : 100-240 VAC, 50/60 Hz
Power Consumption : Max. 270 Watt , Standby <0,5 Watt

Characteristics

Dimensions (W x H x D): 283 x 95 x 222 mm
Weight : 1,9 kg
Audible Noise : 33 dB (A) im Normalmodus
28 dB (A) im ECO-Mode
Projektionsposition : Front-, Back-, Table- und Ceiling projection
Environment : + 0 ~ +40°C / 20 ~ 80 % Humidity
Standard accessory : Remote Control incl. Battery, Power Cable, Quick Start Guide
VGA-Cable, Warranty card,
Optional accessory : Spare bulb, 3D glasses, Carry Bag
Warranty and Service : 36 Months Warranty

