Specifications

Projector specifications



All specifications are subject to change without notice.

GS2 Projector Specifications		
Projection System	DLP 3438	
DMD Type	0.3"	
Native Resolution	1280 x 720 pixels	
Brightness	500 lm	
Contrast Ratio (FOFO)	100,000:1	
Display Color	1.07 Billion Colors	
Aspect Ratio	Native 16:9	
Light Source	Osram Q8A LED	
Light Source Life ⁽¹⁾	20,000 hours (Normal) / 30,000 hours (Eco)	
Throw Ratio	1.3 (35"@IM)	
Zoom Ratio	Fixed	
Keystone Correction	ID, Vertical ± 40 degrees	
Projection Offset	100% ± 5%	
Projection Size (Clear Focus / Maximum)	30 to 100 inches	
SoC	MStar 648	

GS2 Projector Specifications			
os	Android 6.0		
RAM	2G LPDDR3		
Flash	8G EMMC		
WLAN ⁽²⁾	IEEE 802.11 a/b/g/n/ac, 2.4G/5G		
2.4G	A and C SKU	ChI-ChII	
	E SKU		
5 G	A and C SKU	Band I: Ch36, Ch40, Ch44, Ch48	
		Band4: Ch149, Ch153, Ch157, Ch161, Ch165	
	E SKU	Band I: Ch36, Ch40, Ch44, Ch48	
Bluetooth	4.0		
Interface	 USB-A (2.0/1.5A/Reader) x I USB-C™ (DisplayPort 1.2, 5V IA)⁽³⁾ x I HDMI 1.4a x I 3.5mm Audio Out x I Wireless dongle port (WDR02U) Factory Reset Button x I 		
Antenna	Yes		

GS2 Projector Specifications				
Feature	 IPX2, Parental Control, LumiExpert[™], Wireless Projection⁽⁴⁾ (for iOS/macOS[®], for Android[™], for PC), USB-C[™] DisplayPort and USB-A Reader, I5 Degrees Tiling Stand, Auto Focus, Auto Vertical Keystone, 3 Hours Battery 			
Power	DC Supply			
	Frequency	AC 100 to 240V 50/60HZ 1.5A		
	Power Rating	19.0V 3420.0mAh, approximately 65.0VV		
	Battery Life			
	Туре	Lithium-ion battery		
	Electrical Rating	11.1V 6000.0mAh, 66.6W		
	Battery Cycle Life	500 cycles		
	Charging Time	3 hours from 0% to 100%		
	Battery Life	3 hours in battery mode		
Built-in Speaker	2W Chamber x 2			
Resolution Support	VGA (640 x 480) to 1080p (1920 x 1080)			
Horizontal Frequency	15 to 102 KHz			
Vertical Scan Rate	23 to 85 Hz			
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p			

GS2 Projector Specifications		
Video Compatibility	NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM / HDTV	
Dimensions	139 (W) x 144 (H) x 139 (D) mm	
Weight	1.5 Kg	
Noise Level	31 dBA (Normal) / 28 dBA (Eco)	
Working Temperature	0°C to 40°C	
Accessories (Standard)	 Power Adaptor x I Power Cord x I (by region) Wireless Dongle (WDR02U) x I (detachable) Remote Control (with one RC2032 battery) Quick Start Guide Warranty Card (by region) Carry Bag 	
On Screen Display Language	English / French / German / Japanese / Korean / Portuguese / Simplified Chinese / Spanish / Traditional Chinese / Arabic / Hindi / Italian	



- (I): Lamp life results will vary depending on environmental conditions and usage.
- (2): The wireless projection and Bluetooth features are supported by detachable BenQ Wireless Dongle, WDR02U.
 - $^{(3)}$: Maximum resolution: 1080P (1920 * 1080) 60Hz. Maximum data transfer speeds: 2.7Gbps.
 - (4): The performance of WLAN and Bluetooth might be disturbed by distance and obstacles.