

### **Features**

#### **EZWrite 5**

BenQ's EZWrite 5 is the leading annotation solution for interactive and collaborative classroom scenarios. EZWrite's cloud features make it easy for teachers to save files to their personal cloud storage and then access them in any classroom. It also streamlines classroom discussions by making it smoother than ever for teachers and students to share ideas, notes, and opinions as if they are annotating on the same whiteboard regardless of where they are. EZWrite is a cross platform solution that brings together different devices and Operating Systems so everyone can participate.

#### Floating tool

With EZWrite's Floating Tool, teachers can capture screen shots of anything on the screen, including content from apps, websites, and videos from any source. They can then import this content into EZWrite 5 for further discussion and annotation on a brand new page. The Floating Tool is designed to be intuitive and flexible, allowing even the newest user to get the hang of it in seconds, no matter which application or input source they are using.

### **Eye-Care technology**

Eye-Care technology to deliver a zero-flicker viewing experience. The Smart Eye-Care solution can function intuitively with the help of the embedded motion sensor for a smooth and comfortable viewing experience.

#### Hassle-free management

An IT manager's dream, BenQ IFP features both DMS and AMS. BenQ Display Management System (DMS) combines Device Info and Management, Apps Management and OTA (Over-the-Air) Update to provide an ultimate device management solution for greater productivity. BenQ Account Management System (AMS) provides personalized workspace that can be accessed by a simple QR code login. This creates convienence for the use and management of various files. Futhermore, this system provides an efficient and convenient way of managing accounts on BenQ IFPs.

## Input and Output Terminals



USB 3.0 X 2

Connect USB devices such as USB keyboards, USB mice, and USB flash drives

USB 2.0 X 2

Connect USB devices such as USB keyboards, USB mice, and USB flash drives

B IAN

LAN interface, connecting RJ45 terminals. This network port is only used for the closed Android OS on this product.

4 TOUCH

External computer touch signal input.

5 HDMI IN X 3

High-definition multimedia interface signal input. Connect to PC with an HDMI output, a set-top-box, or other video devices capable of realizing touch functions.

6 HDMI IN (MHL) (2.0)

High-definition multimedia interface signal input. Connect to PC with an HDMI output, a set-top-box, or other video devices capable of realizing touch functions.

HDMI OUT

Connect to the display devices with an HDMI input.

8 RS232

Serial interface, used for mutual transfer of data between

9 VGA

Receive analog RGB signals from an external device (such as a computer).

M AUDIO IN

Receive audio signals from an external device.

MIC

Connect to a microphone.

AUDIO OUT

Connect to an earphore





# **Specifications**

| Screen Size   |              | -                                       |               |                            |
|---|--------------|---|---------------|----------------------------|
| Panel   | Panel        |   |               |                            |
| Panel         Contrast Ratio (Typ.)         1100 : 1           Viewing Angle (HV)         178 / 178           Exporse Time (G+C)         8 ms           Backlight Life (Intro)         300000           Operating Hour         181 / 7           Orientation         Landscape           Rever Supply         100V~240V,50 Hz / 60 Hz           Power Supply         100V~240V,50 Hz / 60 Hz           Power Consumption         Maximum (W/h)         500W           Fewer Consumption         Maximum (W/h)         500W           Yell (Wh)         350W         500W           Fewer Consumption         Maximum (W/h)         500W           Yell (Wh)         350W         500W           Fewer Consumption         Maximum (W/h)         500W           Yell (Wh)         350W         500W           Fewer Consumption         Maximum (W/h)         500W           Yell (Wh)         350W         60W           Fower Consumption         Maximum (W/h)         500W           Fewer Consumption         Maximum (W/h)         500W           Yell (Wh)         350W         500W           Fewer Consumption         Maximum (W/h)         500W           Femented Consumer         10  |              |   |               |                            |
| Panel         Vexing Angle (H/V)         ITS / 178           Response Time (G+1-G)         8 mm           Backlight Life (Ins)         3 mm           Operating Hour         I la 17           Orientation         Landscape           Power         Type         Internal           Power Supply         100V~240V,50 Hz / 60 Hz           Power         Power Consumption         Maximum (W/h)         500W           Tipical (W/h)         350W         350W           AC Power Switch         Wes         90 Mm           Wake up         VGA / HDMI / LAN           Touch         Technology, Number of Touches         If R, 20 points           Interface         USB x 2           Glass         Tempered Glass, Hardness         4 mm, 7H           AC cating         Fye-Care         4 mm, 7H           Caring         Fye-Care Solution         Fye-Care           Environment         Pye-Care         No           Environment         Operation Temperature         0 mc 4 mm, 7H           Operation Temperature         0 mc 4 mm         1 mm 7H           Connectivity         VGA         1 mm 10 mm         1 (3.5 mm)           Connectivity         Fig. 1 mm         1 mm 10 mm  |              | 6 (717                                  |               |                            |
| Response Time (G+G)   |              |   |               | 1100 : 1                   |
| Backlight Life (hrs)   30,000   |              | Viewing Angle (H/V)                     |               | 178 / 178                  |
| Operating Hour  |              | Response Time (G-t-G)                   |               | 8 ms                       |
| Power   Power   Power Supply   Power Consumption   Power Supply   Power Consumption   Power Consumption |              | Backlight Life (hrs)                    |               | 30.000                     |
| Type  |              | Operating Hour                          |               | 18 / 7                     |
| Power Apply         Maximum (W/h)         500W           Power Consumption         Maximum (W/h)         500W           Power Application         Maximum (W/h)         500W           Power Switch         Typical (W/h)         350W           AC Power Switch         Yes         Yes           Wake up         Yes         VGA / HDMI/ LAN           Touch         Technology, Number of Touches Interface         IR, 20 points           Interface         USB x 2           Glass         Tempered Glass, Hardness         4mm, 7H           AG Coating         Spe-Care           Eye-Care Solution         Spe-Care           Everage Sultion         Spe-Care           Environment         Operation Temperature         No           Operation Temperature         VGA         XI           Input         XI         XI           Input         XI         XI           Input         XI         XI           Input         XI         XI           Input<  |              | Orientation                             |               | Landscape                  |
| Power                       |              | Туре                                    |               | Internal                   |
| Power         Typical (W/h) (Standby Mode (W/h) (W/h) (0.55W)                               |              | Power Supply                            |               | 100 V~240 V, 50 Hz / 60 Hz |
| Power         Typical (W/h) (Standby Mode (W/h) (W/h) (0.55W)                               | Power        | Power Consumption                       | Maximum (W/h) | 500W                       |
| Standby Mode (W/h)  |              | ·                                       |               | 350W                       |
| March   Mar |              |   | ,, ,          | <0.5W                      |
| AC Power Switch   Yes   VGA / HDMI / LAN     VGA / HDMI / LAN   VGA / HDMI / LAN     VGA / HDMI / LAN   VGA / HDMI / LAN     VGA / HDMI / LAN   VGA / HDMI / LAN     VGA / HDMI / LAN   VGB × 2     VGB × 2     VGB × 2     VGB × 3     VGB × 4     VGB × 5     VGB × 6075     VGC × 6075     VGC × 6076     VGB × 1     VGB × 1  |              |   |               | 0W                         |
| Touch   |              | AC. Power Switch                        |               | Yes                        |
| Touch         Technology, Number of Touches Interface         IR, 20 points           Glass         Tempered Glass, Hardness         USB x 2           Caring         AG coating         AG75           Caring         Eye-Care Solution         Eye-Care           Environment         Operation Semperature         No         OPC           Operating Humidity         VGA         x I         MINDMI         AUDMI         AUDMI <th< td=""><td></td><td></td><td></td></th<>   |              |   |               |                            |
| Interface   | Touch        | •                                       |               |                            |
| Glass         Tempered Glass, Hardness         4mm,7H           AG coating         AG75           Caring         Spe-Care Solution         Eye-Care           Gern-Resistant Screen         No           Environment         Operation Temperature         0°C ~ 40°C           Operating Humidity         20% ~ 80% RH Non-Condensing           Input         VGA         x I           HDMI         MDMI 20 x 3           Audio Input         x I (35)           USB         HDMI         x I (35)           USB         USB 30 x 3         USB 20 x 2           R9232         Yes         Yes           R945         Yes         Yes           Audio         Internal Speaker         16W x 2           Audio         Internal Speaker         16W x 2           Audio         Internal Speaker         16W x 2           Audio         Internal Speaker         17.7 (Top / 51x 1201.8 x 115.8           Audio         Package         2214 x 1358 x 283           Weight (kg)         Screen         99,6           Mechanical         Package         99,6           Mechanical         Wall Mounting (VESA)         800 x 600 mm           (Screen Type / Max Length   |              | C,                                      |               |                            |
| Glass         AG coating         AG75           Caring         Eye-Care Solution         Eye-Care           Carring         Germ-Resistant Screen         No           Chivronment         Operating Humidity         20% ~ 80% RH Non-Condensing           Liput         VGA         x I           Liput         HDMI         HDMI 2.0 x 3           Audio Input         x I (3.5 mm)           Liput         Audio Output         x I (3.5)           Connectivity         USB         USB 3.0 x 3 USB 2.0 x 2           RS232         Yes           RS232         Yes           Remote Controller         Yes           Audio         Internal Speaker         16W x 2           Audio         Package         2214 x 1358 x 283           Weight (kg)         Screen         70,2           Package         99,6           Mechanical         Weight (Will (mm)         Yes           Weight (Will (mm)         Yes   | Glass        |   |               |                            |
| Caring         Eye-Care Solution         Eye-Care           Germ-Resistant Screen         No           Environment         Operation Temperature         0°C ~ 40°C           Operating Humidity         VGA         x I           Input         VGA         x I           HDMI         HDMI 2.0 x 3         HDMI 2.0 x 3           Audio Input         x I (3.5 mm)           HDMI         x I         X.5           USB         USB 3.0 x 3         USB 3.0 x 3           USB 2.0 x 2         Yes         3.0 x 3           RS232         RS232         Yes           Remote Controller         Yes           Audio         Internal Speaker         I6W x 2           Dimension (mm)         Screen         1957.1 x 1201.8 x 115.8           Package         2214 x 1358 x 283           Weight (kg)         Screen         70.2           Weight (kg)         Screen         70.2 </td <td>· ·</td> <td></td> <td>V -</td>   |              | · ·                                     |               | V -                        |
| Caring         Germ-Resistant Screen         No           Environment         Operation Temperature         0°C ~ 40°C           Operating Humidity         VGA         x I           Linguity         Mode         Mode           Linguity         Mode         x I           Linguity         Mode         Mode           Linguity         Mode         x I           Connectivity         Mode         Linguity         x I           Linguity         Mode         Mode         Linguity           Connectivity         Mode         Linguity         X I           Linguity         Mode         X I         X I           Linguity         Mode         X I         X I           Linguity         Mode         X I         X I         X I           Linguity         Mode         X I         X I         X I         X I         X I         X I         X I         X I<  |              | 9                                       |               |                            |
| Deration Temperature         0°C ~ 40°C           Operating Humidity         20% ~ 80% RH Non-Condensing           Input         VGA         x I           HDMI 2.0 x 3         Audio Input         x I (3.5 mm)           Audio Input         x I (3.5 mm)           HDMI 2.0 x 3         X I           Audio Output         x I (3.5)           USB         USB 3.0 x 3           USB 2.0 x 2         USB 2.0 x 2           RS232         Yes           RP45         Yes           Remote Controller         Yes           Audio         Internal Speaker         I6W x 2           Audio         Internal Speaker         I6W x 2           Audio         2214 x 1358 x 283           Weight (kg)         Screen         1957.1 x 1201.8 x 115.8           2214 x 1358 x 283         2214 x 1358 x 283           Weight (kg)         Screen         70.2           Package         99.6           Mechanical         Bezel Width (mm)         I7.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA)         Wall Mounting (VESA)         800 x 6000 mm           (Screw Type / Max. Length)         Yes  |              | •                                       |               | ,                          |
| Environment         Operating Humidity         VGA         x 1           Input         HDMI         HDMI 20 x 3           HDMI         x 1 (3.5 mm)           Connectivity         HDMI         x 1 (3.5 mm)           LVSB         HDMI         x 1 (3.5)           RS232         Yes           RJ45         Yes           Remote Controller         Yes           Audio         I6W x 2           Package         16W x 2           Package         2214 x 1358 x 283           Weight (kg)         Screen         1957.1 x 1201.8 x 115.8           Package         2214 x 1358 x 283           Mechanical         Bezel Width (mm)         Screen         70,2           Wall Mounting (VESA)         Screen         17.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA)         Screen         17.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA)         M8 x 25 mm           OPS         Yes  |              |   |               |                            |
| Input   |              |   |               |                            |
| HDMI  | Connectivity | , ,                                     | V/C A         | <u> </u>                   |
| Audio Input         x I (3.5 mm)           Connectivity         HDMI         x I (3.5)           Connectivity         USB         USB 3.0 x 3 USB 2.0 x 2           USB         RS232         Yes           Remote Controller         Yes           Audio         Internal Speaker         I6W x 2           Audio         Internal Speaker         I6W x 2           Package         2214 x 1358 x 283           Weight (kg)         Screen         Package         2214 x 1358 x 283           Mechanical         Bezel Width (mm)         Screen         99,6           Mechanical         Bezel Width (mm)         I7.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA) (Screw Type / Max. Length)         800 x 600 mm M8 x 25 mm           OPS         Yes   |              | прис                                    |               |                            |
| Connectivity         HDMI   |              |   |               |                            |
| Connectivity         Audio Output         x 1 (3.5)           USB 3.0 x 3 USB 2.0 x 2         USB 2.0 x 2           RS232         Yes           RJ45         Yes           Remote Controller         Yes           Audio         Internal Speaker         16W x 2           Dimension (mm)         Screen         1957.1 x 1201.8 x 115.8           Package         2214 x 1358 x 283           Weight (kg)         Screen         70,2           Package         99,6           Mechanical         Bezel Width (mm)         17.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA) (Screw Type /Max. Length)         800 x 600 mm M8 x 25 mm           OPS         Yes  |              |   |               | ,                          |
| USB   USB   USB   USB   USB   2.0 x 2     R5232   Yes     RJ45   Yes     Remote Controller   Yes     Audio   Internal Speaker   I6W x 2     Dimension (mm)   Screen   1957.1 x 1201.8 x 115.8     Package   2214 x 1358 x 283     Weight (kg)   Screen   70,2     Package   99,6     Mechanical   Bezel Width (mm)   17.7 (Top / Side), 87.7 (Bottom)     Wall Mounting (VESA) (Screw Type /Max. Length)   OPS   Yes     OPS   Yes   Yes     USB 3.0 x 3  |              |   |               |                            |
| RS232   Yes     RJ45   Yes     Remote Controller   Yes     Audio   Internal Speaker   I6W × 2     Dimension (mm)   Screen   Package   2214 × 1358 × 283     Weight (kg)   Screen   70,2     Package   99,6     Mechanical   Bezel Width (mm)   I7.7 (Top / Side), 87.7 (Bottom)     Wall Mounting (VESA) (Screw Type /Max.Length)   OPS   Yes     OPS   Yes   Yes     OPS   Yes   Weight (Max   Max 25 mm   Max |              | 1.100                                   | Audio Output  |                            |
| RS232   Yes     RJ45   Yes     Remote Controller   Yes     Audio   Internal Speaker   I6W × 2     Dimension (mm)   Screen   1957.1 × 1201.8 × 115.8     Package   2214 × 1358 × 283     Weight (kg)   Screen   70,2     Package   99,6     Mechanical   Bezel Width (mm)   17.7 (Top / Side), 87.7 (Bottom)     Wall Mounting (VESA) (Screw Type /Max. Length)   N8 × 25 mm     OPS   Yes   |              | USB                                     |               |                            |
| Medio       Ry45       Yes         Audio       Internal Speaker       16W × 2         Dimension (mm)       Screen       1957.1 × 1201.8 × 115.8         Package       2214 × 1358 × 283         Weight (kg)       Screen       70,2         Package       99,6         Mechanical       Bezel Width (mm)       17.7 (Top / Side), 87.7 (Bottom)         Wall Mounting (VESA) (Screw Type /Max. Length)       800 × 600 mm (M8 x 25 mm         OPS       Yes   |              | DC222                                   |               |                            |
| Audio         Internal Speaker         I6W × 2           Audio         Dimension (mm)         Screen         1957.1 × 1201.8 × 115.8           Package         2214 × 1358 × 283           Weight (kg)         Screen         70,2           Package         99,6           Mechanical         Bezel Width (mm)         17.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA) (Screw Type /Max. Length)         800 × 600 mm (M8 × 25 mm           OPS         Yes  |              |   |               |                            |
| Audio         Internal Speaker         I6W × 2           Dimension (mm)         Screen         1957.1 × 1201.8 × 115.8           Package         2214 × 1358 × 283           Weight (kg)         Screen         70,2           Package         99,6           Mechanical         Bezel Width (mm)         17.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA) (Screw Type /Max. Length)         800 × 600 mm (M8 × 25 mm           OPS         Yes  |              | ,                                       |               |                            |
| Dimension (mm)   Screen   1957.1 × 1201.8 × 115.8     Package   2214 × 1358 × 283     Weight (kg)   Screen   70,2     Package   99,6     Mechanical   Bezel Width (mm)   17.7 (Top / Side), 87.7 (Bottom)     Wall Mounting (VESA)   800 × 600 mm     (Screw Type /Max. Length)   M8 × 25 mm     OPS   Yes  | A 1.         |   |               |                            |
| Package   22.14 x 1358 x 283     Weight (kg)   Screen   70,2     Package   99,6     Mechanical   Bezel Width (mm)   17.7 (Top / Side), 87.7 (Bottom)     Wall Mounting (VESA)   800 x 600 mm     (Screw Type /Max. Length)   M8 x 25 mm     OPS   Yes   | Audio        |   | · ·           |                            |
| Weight (kg)         Screen Package         70,2 99,6           Mechanical         Bezel Width (mm)         17.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA) (Screw Type /Max. Length)         800 x 600 mm M8 x 25 mm           OPS         Yes  | Mechanical   | Dimension (mm)                          |               |                            |
| Mechanical         Bezel Width (mm)         17.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA)<br>(Screw Type /Max. Length)         800 x 600 mm<br>M8 x 25 mm           OPS         Yes   |              | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\  | <u> </u>      |                            |
| Mechanical         Bezel Width (mm)         17.7 (Top / Side), 87.7 (Bottom)           Wall Mounting (VESA)<br>(Screw Type /Max. Length)         800 x 600 mm<br>M8 x 25 mm           OPS         Yes   |              | VVeight (kg)                            |               |                            |
| Wall Mounting (VESA)         800 x 600 mm           (Screw Type /Max. Length)         M8 x 25 mm           OPS         Yes  |              |   | Package       |                            |
| (Screw Type / Max. Length) M8 x 25 mm  OPS Yes  |              | ` '                                     |               |                            |
| OPS Yes   |              |   |               |                            |
|   |              | , |               |                            |
| Pen Iray Yes  |              |   |               |                            |
|   |              | ren Iray                                |               | Tes                        |

# Dimension (mm)











