







Smart IP Al Conference Cam All-in-one Conference Cam

Al Technology for Face Detection VB392+ ConferenceCam provides you with a true face-to-face meeting experience by delivering 2K resolution video with crystal image. Powered by cutting-edge Al technology, VB392+ video conferencing system automatically focuses on the current speaker. When there are different active speakers involved, it can focus on all participants into one video conferencing room. Al Intelligent ConferenceCam which have 4x builts-in omnidirectional mics and 1x full dupiex speaker. It ensures to pickup the sounds on 360 degree, the pickup range can up to 16.4 ft based on noise reduction and Echo cancellation technology. VB392+ allow you to easily see everyone's face and hear what they say clearly with the integrated audio system. Driver free, USB plug & play connectivity, this ConferenceCam is suitable for huddle and medium rooms.

VB392+ ConferenceCam ensures all remote participants to enjoy an real face-to-face meeting experience, ideally compatible with the main video calling apps or platform video like Skype, OBS, Microsoft Team, Cisco WebEx, Zoom, Slack, GoToMeeting etc. And it is compatible with Windows 7/8/10, MacOS & IOS, Linux, ChromeOS, and Android systems.

- Compactable all-in-one design
- Al Technology for Face Detection
- 1/3 CMOS Sensor (GC4663), 2.88mm wide view angle
- 5m (16.4 ft) audio pickup radius with noise and echo cancellation
- Plug & play USB connectivity
- FOV 90 degree, vertical 30 degree
- 2K (2560*1440) 60fps resolution, 4 Mega Pixel
- 4 x digital silicon microphones & 1x 50*50MM full band speaker

Features















Compatible | Software

Details



Supports 2K/1080P/720P HD video calling; Supports face detection according to your voices and movements.



All-in-one smart video conferenceCam intergrate the camera, mics and speaker in one device, the audio pickup range can up 16.4 ft with 360 degree.



Advanced Al intelligent conferenceCam with a 90° horizontal and 30° vertical field of view ensures that the entire group is visible.



Driver free, simply plug the Smart IP video conferenceCam into PC via USB port, start meeting with your familiar video applications, supports Windows 7/8/10, Mac OS & IOS, Linux, ChromeOs, and Android systems.

Product Specifications	
Sensor Type: GC4663(1/3")	OUT PUT S.P.L: 82+3dB
Pixel Mega: 4 Mega Pixel (2K Resolution)	Distortion(THD): 0.2%
Focal Length: 2.88mm	Distortion Rate: 5% Max
Al Recognition: Face Detection	Effective Bandwidth: F0-20KHz Average SPL-10dB
FOV: 90 Degree	Touch Control Type: Capacitive Touch
Vertical Angle: +15 Degree	Version: USB
Microphone: Built-in 4 x Digital Silicon Mics	Agreement Support: UVC
Speakerphone: 1x 50*50MM Full Band Speaker	Interface Port: Type-C
LED: 16x LEDs, Annular Array, RGB-LEDs	Audio Pickup Range: 5 Meters(16.4ft) Radius
Button: 5x Buttons; Al Nolume +- / Mute	Size: 260*70*70(mm)
Sensitivity(S): -27dBFS	Neight Weight: 550g
SNR: 64.3dB(A)	Accessories: USB Cable(3m), User's Manual
Lowest Resonance Frequency: 180Hz+20%	



