



SMART IP SPEAK 610

Speakerphone

Model: SPEAK610





SPEAK610 Smart IP Speak 610

SPEAK610 series USB/Bluetooth speakerphone is a business grade conference call audio equipment. It Built-in 3 high-performance omni-directional microphone. USB2.0 connection to PC for web-conferencing, video conferencing and easy Bluetooth® connection to tablets and mobile phones. can instantly replace the PCs and laptop's speaker and microphone with crystal clear sound without any echoes or distortions. It is suitable for small enterprises, home office, professionals, on-line education teachers and students, and business travelers for personal or small group conference calls

- **USB cable and bluetooth**
USB2.0 connection to PC for web-conferencing, video conferencing and easy Bluetooth® connection to tablets and mobile phones.
- **Crystal clear sound for efficient meetings**
Ensure everyone experiences clear sound with 3 built-in Omni-directional microphone within 3m radios
- **Digital Signal Processing (DSP) technology**
Echo cancellation and noise reduction provides Crystal clear sound without any echoes or distortions.
- **Full duplex Microphone**
Excellent full duplex bi-directional conversation provides outstanding audio output.
- **LED indicators**
When the speakerphone connects to the power, the blue light will bright, and when you press the bluetooth key, the green light will bright.

Features |




Portable design



3 m sound-pickup diameter



Echo cancellation and noise reduction



Compatible software




USB & Bluetooth connection



Speakerphone for small meeting



Built-in Omni-directional microphones



360 degree pick up radios

Product Specifications

Recommended parameters	Connection Interface
Room size: 10-15m ²	USB Interface: Yes
Participants: 3-5	Bluetooth connection: Yes
Microphone parameter	Package
Pick up distance: 3M	Product size: 140 x 32mm
Response frequency: 30-16KHz Built-in microphone: 3	Packing size: 245x170x50mm
Extended microphone: no / not expandable	Weight: 0.5kg
Speaker	Accessory: USB cable Carrying case manual
Maximum output (dB) : 83dB	Operating environment
Response frequency: 30-16KHz	Applicable system: windows XP, windows Vista, windows 7/8/10
Audio	Power: USB: 5 V DC @ 300 mA Maximum
Full duplex: Support	Working temperature: 5°C-40°C
Noise suppression (DNR): Support	Storage temperature: -30°C-55°C
Automatic Gain (AGC) : Support	Built-in battery: N/A
Standards	Standards: FCC / CE / RoHS
FCC / CE / RoHS	