



Bluetooth Speakerphone

Model: SPEAK610BT





SPEAK610BT Smart IP Speak 610-BT

SPEAK610 series USB/Bluetooth speakerphone is a business grade conference call audio equipment. It Built-in 3 high-performance omni-directional microphone. USB2.0 connection to PC for web-conferencing, video conferencing and easy Bluetooth® connection to tablets and mobile phones. can instantly replace the PCs and laptop's speaker and microphone with crystal clear sound without any echoes or distortions. It is suitable for small enterprises, home office, professionals, on-line education teachers and students, and business travelers for personal or small group conference calls

USB cable and bluetooth
 USB2.0 connection to PC for web-conferencing, video conferencing and easy Bluetooth® connection to tablets and mobile phones.



- Crystal clear sound for efficient meetings
 Ensure everyone experiences clear sound with 3 built-in Omni-directional microphone within 3m radios
- Digital Signal Processing (DSP) technology
 Echo cancellation and noise reduction provides Crystal clear sound without any echoes or distortions.
- Full duplex Microphone

 Excellent full duplex bi-directional conversation provides outstanding audio output.
- LED indicators
 When the speakerphone connects to the power, the blue light will bright, and when you press the bluetooth key, the green light will bright.







3 m sound-pickup diameter



noise reduction



Details

Echo cancellation and Compatible software








Speakerphone for small meeting



microphones



Built-in Omni-directional 360 degree pick up radios

Product Specifications	
Recommended parameters	Connection Interface
Room size: 10-15m2	USB Interface: Yes
Participants: 3-5	Bluetooth connection: Yes
Microphone parameter	Package
Pick up distance: 3M	Product size: 140 x 32mm
Response frequency: 30-16KHz Built-in microphone: 3	Packing size: 245x170x50mm
Extended microphone: no / not expandable	Weight: 0.5kg
Speaker	Accessory: USB cable Carrying case manual
Maximum output (dB) : 83dB	Operating environment
Response frequency: 30-16KHz	Applicable system: windows XP, windows Vista,
Audio	windows 7/8/10
Full duplex: Support	Power: USB: 5 V DC © 300 mA Maximum
Noise suppression (DNR): Support	Working temperature: 5°C-40°C
Automatic Gain (AGC) : Support	Storage temperature: -30°C-55°C
Standards	Built-in battery: N/A
FCC / CE / RoHS	Standards: FCC / CE / RoHS



