



SPECIFICATIONS

	Smart IP -3A86
Technology	IR - Infrared Image Sensor System
Size	86"
Touches	10
Support	Finger, Pen, Pointer or any Opaque Object
Dimensions(mm)	1788 x 1281 x 39.5
Active Area(mm)	1732 x 1255
Active Size(inch)	85
Touch Accuracy	<2mm
Resolution	32768 X 32768
Response Time	Appx 8ms
Aspect Ratio	4:3
Surface Material	Nano/Ceramic , Cold Rolled Steel, Anti Damage
Wick Material	High Density Polyfoam
Back Material	Galvanized Steel Sheet
Certifications	CE, FCC, RoHS
Software	EdStudio and Calibration Software
Optional Software	-
Interface	USB1.1, USB2.0, USB3.0
Cursor Speed / Scan Time / Sampling Rate	180 dots/points per second
Driver Support (OS)	Windows 2000 – Windows 10, Linux, Mac, Android
Operation Temperature (°C)	-10-45°C
Operation Humidity (%)	10~90%
Storage Temperature (°C)	-30-60°C
Storage Humidity (%)	0~95%
L X W X H (mm)	1788 x 1281 x 39.5
Power Supply	USB
Working Voltage	DC 5V ±5%
Working Current	100mA