

# Specifications

## Projector specifications



All specifications are subject to change without notice.

Specifications	
Projection System	DLP
DMD Type	0.23"
Native Resolution	1280 x 720 pixels
Brightness	300 ANSI Lumens
Contrast Ratio	100,000:1
Display Color	30 Bits (16.7 Billion Colors)
Aspect Ratio	16:9
Light Source	Osram LED
Light Source Life <sup>(1)</sup>	20,000/30,000 hours (Normal/Eco)
Throw Ratio	1.2 (37.6"@1M)
Zoom Ratio	Fixed
Keystone Correction	Auto Vertical $\pm$ 40 Degrees
Projection Offset	100% $\pm$ 5%
Projection Size	30 to 100 inches

Specifications		
Interface	<ul style="list-style-type: none"> <li>• USB-C (DisplayPort 1.2)(5V/1.5A) x 1</li> <li>• HDMI 1.4b (w/o 3D) x 1</li> <li>• 3.5mm Audio Out x 1</li> </ul>	
Power	<b>DC Supply</b>	
	Frequency	AC 100 to 240V 50/60HZ 1.5A
	Power Consumption	42W/34W/29W (Normal/Eco/Low Power)
	<b>Battery</b>	
	Type	Lithium-ion battery
	Capacity	4800mAh/11.1V
	Battery Life Cycle	500 cycles
	Battery Life	2.5 hours
Built-in Speaker	4W x 2 + 8W Woofer, 2.1 Channels Chamber Speakers	
Resolution Support	HDMI: up to 3840 x 2160@30 USB-C: up to 1920 x 1080@60	
Horizontal Frequency	15 to 102 KHz	
Vertical Scan Rate	23 to 85 Hz	
Noise Level (Normal/Eco)	29dBA/27dBA	
HDTV Compatibility	23 to 85 Hz	
Operating Temperature	0 to 40 °C	
Storage Temperature	-20 to 60 °C	
Operating / Storage Relative Humidity	10% to 90% (without condensation)	