ABTYRE LES WERE AND A LES WERE AND A



RM8603 Interactive Displays





ClassroomCare® Technology - Unique health prevention

package: BenQ displays are the only ones with the double certification from TÜV and SIAA for approved efficacy and human safety. While the Eye-Care safeguards the users' vision, Germ-Resistant Screen and Stylus
Pen are effective to avoid the spread of germs.



The new and upgraded software EZWrite 6 comes with innovative features: the users can whiteboard without problems. Teachers share their works from the interactive display, while every student can collaborate and work together with their own devices, without installing any software. With this tool, hybrid learning becomes an easy reality.




To oversee accounts on BenQ's displays, **the hassle-free Management** includes the **Display Management System (DMS)** and the **Account Management Systems (AMS).** While AMS provides personalised workspaces, the DMS let IT control all the devices

→ Specifications subject to change without notice. Please contact your local BenQ office for the full BenQ product range.


in the campus.

Panel	Screen Size		86"
	Resolution		4K UHD 3840 x 2160
	Brightness (Typ.)		450 nits
	Contrast Ratio (Typ.)		1200 : 1
	Viewing Angle (H/V)		178° / 178°
	Response Time (G-t-G)		8 ms
	Backlight Life (hrs)		50,000
	Panel Surface		AG, Haze 25%
	Operating Hour		18 hrs / 7 days
	Orientation		Landscape
Platform Solution	System Memory		8GB
Flatform Solution	Storage		32GB
	OS		Android 9.0
Power	Power Supply		100V~240V, 50-60Hz
	Power	Maximum (W/h)	488.2
	Consumption	Typical (W/h)	180
			<0.5
		Standby Mode (W/h)	Built-in
	AC Power Switch		
	Wake up		LAN / HDMI / VGA / DP
Touch	Technology		Infrared
	Number of Touch Points		20 Points
	Interface		USB Type B x 3
Glass ClassroomCare® Technology	Tempered Glass		3.2 mm
	Hardness		9H
	AG coating		Yes
	Eye-Care Solution		Yes
Classi comcare w recimology	Air-Quality Sensor		No
	Germ-Resistant Screen		Yes
Environment	Operation Temperature		0°C~40°C
	Operating Humidity		10% ~ 90% RH Non-Condensing
	Energy Efficiency		Energy 8.0 Certified
C 1	Input	VGA	x l
Connectivity	input	DVI	No
		HDMI 2.0	× 3
		HDMI 2.0 Display Port 1.2	x 3 x 1
		HDMI 2.0 Display Port 1.2 Audio Input (3.5mm)	x 3 x 1 x 1
	Output	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA	x 3 x 1 x 1 No
	Output	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI	x 3 x I x I No No
	Output	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0	x 3 x I x I No x I
	Output	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort	x 3 x 1 x 1 No No X 1 No
	·	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output	x 3 x 1 x 1 No No No No
	Output USB	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A	x 3 x x No No x No x 7 (2.0 x 2 / 3.0 x 5)
	·	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B	x 3 x I x I No x I No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1)
	USB	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A	x 3 x 1 x 1 No No x 1 No X 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1
	USB RS232	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B	x 3 x 1 x 1 No No x 1 No X 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 1 x 1
	USB	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B	x 3 x 1 x 1 No No x 1 No X 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1
	USB RS232	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C	x 3 x 1 x 1 No No x 1 No X 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 1 x 1
Audio	USB RS232 RJ45	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C	x 3 x x No No X No X 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x x x 2
	USB RS232 RJ45 Remote Controller Internal Speaker	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C	x 3 x x No No x 1 No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1 x 1 x 2 x 1 16W x 2
Audio Mechanical	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm)	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C	x 3 x 1 x 1 No No x 1 No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1 x 1 x 1 x 1 x 2 x 2 x 1 x 1 x 1 x 2 x 1 x 1 x 2 x 1 x 1 x 2 x 1 x 1 x 2 x 1 x 3 x 3 x 3 x 3 x 3 x 3 x 3 x 3
	USB RS232 RJ45 Remote Controller Internal Speaker	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type B Type C Screen Net Weight	x 3 x 1 x 1 No No x 1 No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1 x 1 x 1 x 1 x 2 x 1 16W x 2 1962 x 1203 x 121
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg)	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C	x 3 x 1 x 1 No No X 1 No X 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 1 x 2 x 1 16W × 2 1962 × 1203 × 121 68.5 89.5
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm)	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C	x 3 x x No No × 1 No No x 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 1 x 2 x 1 16W × 2 1962 × 1203 × 121 68.5 89.5 16.6 / 16.6 / 16.6 / 16.6
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA)	x 3 x 1 x 1 No No X 1 No X 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 1 x 2 x 1 16W × 2 1962 × 1203 × 121 68.5 89.5
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max.	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA)	x 3 x 1 x 1 No No x 1 No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1 x 1 x 1 x 2 x 1 16W x 2 1962 x 1203 x 121 68.5 89.5 16.6 / 16.6 / 16.6 / 16.6 60 x 400 (4 holes); 4 – M8*20L
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max. Wall Mount Kit	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA)	x 3 x 1 x 1 No No X 1 No No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1 x 1 x 2 x 1 16W x 2 1962 x 1203 x 121 68.5 89.5 16.6 / 16.6 / 16.6 / 16.6 600 x 400 (4 holes); 4 – M8*20L Included
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max. Wall Mount Kit OPS Slot	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA)	x 3 x 1 x 1 No No x 1 No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1 x 1 x 2 x 1 16W x 2 1962 x 1203 x 121 68.5 89.5 16.6 / 16.6 / 16.6 / 16.6 600 x 400 (4 holes); 4 – M8*20L Included Yes
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max. Wall Mount Kit OPS Slot NFC sensor	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA)	x 3 x 1 x 1 No No x 1 No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1 x 1 x 2 x 1 16W x 2 1962 x 1203 x 121 68.5 89.5 16.6 / 16.6 / 16.6 / 16.6 600 x 400 (4 holes); 4 – M8*20L Included Yes No
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max. Wall Mount Kit OPS Slot NFC sensor Pen Tray	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA) Length)	x 3 x 1 x 1 No No x 1 No x 7 (2.0 x 2 / 3.0 x 5) x 3 (2.0 x 2 / 3.0 x 1) x 1 x 1 x 1 x 1 x 2 x 2 x 1 16W x 2 1962 x 1203 x 121 68.5 89.5 16.6 / 16.6 / 16.6 600 x 400 (4 holes); 4 – M8*20L Included Yes No Yes
	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max. Wall Mount Kit OPS Slot NFC sensor	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA) Length)	x 3 x 1 x 1 No No x 1 No x 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 1 x 1 x 2 x 2 x 1 16W × 2 1962 × 1203 × 121 68.5 89.5 16.6 / 16.6 / 16.6 600 × 400 (4 holes); 4 – M8*20L Included Yes No Yes InstaShare 2
Mechanical	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max. Wall Mount Kit OPS Slot NFC sensor Pen Tray	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA) Length)	x 3 x 1 x 1 No No X 1 No No x 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 2 x 1 16W × 2 1962 × 1203 × 121 68.5 89.5 16.6 / 16.6 / 16.6 / 16.6 600 × 400 (4 holes); 4 – M8*20L Included Yes No Yes InstaShare 2 EZ Write 6.0
Mechanical	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max. Wall Mount Kit OPS Slot NFC sensor Pen Tray Wireless Presentat	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA) Length)	x 3 x 1 x 1 No No x 1 No x 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 1 x 1 x 2 x 2 x 1 16W × 2 1962 × 1203 × 121 68.5 89.5 16.6 / 16.6 / 16.6 600 × 400 (4 holes); 4 – M8*20L Included Yes No Yes InstaShare 2
Mechanical	USB RS232 RJ45 Remote Controller Internal Speaker Dimension (mm) Weight (kg) Bezel Width (mm) Wall Mounting (VE (Screw Type /Max. Wall Mount Kit OPS Slot NFC sensor Pen Tray Wireless Presentat Whiboarding	HDMI 2.0 Display Port 1.2 Audio Input (3.5mm) VGA DVI HDMI 2.0 DisplayPort Audio Output Type A Type B Type C Screen Net Weight Gross Weight SA) Length)	x 3 x 1 x 1 No No X 1 No No x 7 (2.0 × 2 / 3.0 × 5) x 3 (2.0 × 2 / 3.0 × 1) x 1 x 2 x 1 16W × 2 1962 × 1203 × 121 68.5 89.5 16.6 / 16.6 / 16.6 / 16.6 600 × 400 (4 holes); 4 – M8*20L Included Yes No Yes InstaShare 2 EZ Write 6.0


INPUT AND OUTPUT TERMINALS



DIMENSION (MM)



STYLUS PEN



The RM03 Series comes with a pair of BenQ's germresistant pens that allows you to write in different colours without any interruptions.

Benq

© 2021 BenQ Corp. Specifications may vary by region, please visit your local stores for details. Actual product's features and specifications are subject to change without notice. This material may include corporate names and trademarks of third parties which are the properties of the third parties respectively.





www.benq.eu/en-eu/business/index.html

Just Projectors, 7 Campbell Court, Bramley, Hampshire, RG26 5EG